

Introducing the latest *STANDARD* features on the Natmar Easy Seal AV and Easy Seal!

****Temperature and air pressure variance shutdown****



Easy Seal III AV
Model HS177
(automatic pivot)

Unexpected or unauthorized changes in temperature or pressure will cease machine operation to prevent improper sealing of labels and emblems.



Easy Seal III
Model HS175
(manual pivot)

Other NEW Features of the HS177 / HS175

- Temperature lock out can be field activated
- Simplified wiring
- Easy adjustable air switch to meet pressure requirements of various label types
- Platens must be aligned before upper platen can descend
- Adjustable vertical speed of upper platen

Standard Maintenance Features

- 120 volts or 220 volts
- Complete operations manual with each machine
- Extensive troubleshooting section in manual
- Heavy use of non customized electrical parts
- One year warranty of parts and labor (excluding supply parts – teflon, covers and rubber pads)

Standard Production Features

- Automatic pivoting upper platen (HS177)
- Manually pivoting upper platen (HS175)
- Dual start control
- 4" x 6" upper and lower heated platens
- Teflon covers on all platens or pads bonded to aluminum plate
- Heavy duty self-lubricating 4" air cylinder
- Time, temperature and pressure lockout/shut-down devices
- Dual digital display heat controller for each platen

Standard Safety Features

- Full circuit touch safety bar with automatic shutdown
- Operation delay after touch bar activation
- Two hand activation with anti tie-down
- Bumper guards surrounds lower platens
- Plexiglas guard covers pinch point between upper platen and hood
- Emergency stop buttons



Natmar Services Company
Phone: 1-800-798-8206
Fax: 1-315-445-8046

139 Beattie Street
Syracuse, NY 13224
info@natmar-nsc.com